LMD NBR

Cleaning Hose

Application:

- Suitable for steam and hot water cleaning purposes and for conveying liquid products such as milk.
- Suitable for use in dairies, slaughterhouses and in the food industry.

Standard/approval:

BfR (former BgVV) XXI:2002 (Kat. 2), FDA (CFR 21 §177.2600).

Notice:

- S For applications of cleaning agents, please see our separate information sheet.
- Other lengths (>40m) on request.



Temperature range: $-35^{\circ}\text{C} / +100^{\circ}\text{C}$ hot water $/ +164^{\circ}\text{C}$ saturated steam.

Safety factor: Steam: 10:1, hot water: 3:1

Tube: NBR, white, smooth, food quality, resistant to temperature and cleaning agents.

Reinforcement: Textile braided.

Cover: NVC, blue, resistant to abrasion, grease and oil, smooth.

Marking: Continuous coloured marking, white:
"SEMPERIT S LMD - NBR Lebensmittel/Heisswasser/Food/Hot Water PN 20 bar 100°C FDA, BfR XXI
KAT2 Dampf/Steam PN 6 bar 164°C".

Article number	Internal-Ø in		Wall width	External-Ø	Work. pressure (max.) bar		Number of inserts	Bending radius	Weight	Coil length
	mm	inches	in mm	in mm	Satur. steam	Hot water		(min.) in mm	approx. kg/m	(max.) m
68255 1350	13,0	1/2	5,0	23,0	6	20	1	65	0,35	40
68255 1650	16,0	5/8	5,0	26,0	6	20	1	85	0,45	40
68255 1960	19,0	3/4	6,0	31,0	6	20	1	100	0,60	40
68255 2560	25,0	1	6,0	37,0	6	20	1	125	0,80	40

Please note: General information about our range of products can be found in the appendix to this catalogue. Before using with new or untested media, or before using in applications that are not covered in the product information, written advice must first be obtained from a specialist dealer or a Semperit application engineer. All products must be inspected regularly for operational safety. For safety reasons, hoses must be replaced in the event of damage, especially if the cover is damaged. All products must be stored and maintained according to our storage, care and maintenance instructions, and according to DIN 7716:1982.

We are constantly developing and improving our products for our customers. For the latest product information, please visit our website www.semperflex.com regularly or contact one of our specialist dealers or Semperit application engineers. Contracts are agreed according to our general terms and conditions. Subject to change without notice.

Important notice: This catalogue has been prepared with the greatest care in order to provide you with all the information you need. The information contained herein incorporates the latest state-ofthe-ort technology, and is the result of triads and tests carried out over many years, or conforms to the resistance requirements of the media listed as set out in ISO TR 7620:2005[E]. The individual conditions of use affect the use of each product. They herefore only ensure the safety that can be expected assuming that the specifications in our written product information, the specifications regarding resistance to chemicals and our cleaning procedures are all complied with. We cannot guarantee this level of safety in the event of improper handling, e.g. squashing, rupturing, stretching or filling with media that are not permitted. Unless specified otherwise, all hoses are manufactured to EN ISO 1307:2006.

