

SM40

Grout & Plaster Hose



Application:

- Ⓢ For conveying grout, screed, plaster and gypsum in compact flow process.

Feature:

- Ⓢ Very long service life due to abrasion resistant quality of the rubber tube and cover.
- Ⓢ The compact reinforcement package provides a very stable cross-section making the hose highly kink resistant and also offers high pressure resistance.
- Ⓢ Antistatic construction prevents the build-up of static electricity.

Notice:

- Ⓢ On request:
 - with harder rubber quality and higher pressure resistance
 - with steel wire braid
 - with fire resistant cover
 - with several cover colours.



Temperature range: -35°C / +80°C.

Safety factor: 2.5 : 1

Tube: SBR/NR/BR, black, smooth, abrasion resistant, antistatic.

Reinforcement: Textile wrapped.

Cover: SBR, black, antistatic, cloth impression.

Marking: Continuous transfer tape, yellow: "SEMPERIT S SM40 Mörtel/Plaster PN 40 bar".

Article number	Internal-Ø in		Wall width in mm	External-Ø in mm	Work. pressure (max.) bar	Number of inserts	Bending radius (min.) in mm	Weight approx. kg/m	Coil length (max.) m
	mm	inches							
48386 1960	19,0	3/4	6,0	31,0	40	2	190	0,60	40
48386 2560	25,0	1	6,0	37,0	40	4	220	0,75	40
48386 2570	25,0	1	7,0	39,0	40	4	250	0,80	40
48386 3270	32,0	1 1/4	7,0	46,0	40	4	320	1,10	40
48386 3570	35,0	1 3/8	7,0	49,0	40	4	350	1,15	40
48386 3575	35,0	1 3/8	7,5	50,0	40	4	350	1,20	40
48386 3880	38,0	1 1/2	8,0	54,0	40	4	380	1,40	40
48386 3810	38,0	1 1/2	10,0	58,0	40	4	380	1,90	40
48386 4075	40,0		7,5	55,0	40	4	350	1,35	40
48386 5080	50,0		8,0	66,0	40	4	500	1,70	40
48386 5090	50,0		9,0	68,0	40	4	500	1,95	40
48386 5010	50,0		10,0	70,0	40	4	500	2,20	40
48386 6590	65,0		9,0	83,0	40	4	650	2,55	40

Please note: General information about our range of products can be found in the appendix to this catalogue. Before using with new or untested media, or before using in applications that are not covered in the product information, written advice must first be obtained from a specialist dealer or a Semperit application engineer. All products must be inspected regularly for operational safety. For safety reasons, hoses must be replaced in the event of damage, especially if the cover is damaged. All products must be stored and maintained according to our storage, care and maintenance instructions, and according to DIN 7716:1982. We are constantly developing and improving our products for our customers. For the latest product information, please visit our website www.semperflex.com regularly or contact one of our specialist dealers or Semperit application engineers. Contracts are agreed according to our general terms and conditions. Subject to change without notice.

Important notice: This catalogue has been prepared with the greatest care in order to provide you with all the information you need. The information contained herein incorporates the latest state-of-the-art technology, and is the result of trials and tests carried out over many years, or conforms to the resistance requirements of the media listed as set out in ISO TR 7620:2005(E). The individual conditions of use affect the use of each product. They therefore only ensure the safety that can be expected assuming that the specifications in our written product information, the specifications regarding resistance to chemicals and our cleaning procedures are all complied with. We cannot guarantee this level of safety in the event of improper handling, e.g. squashing, rupturing, stretching or filling with media that are not permitted. Unless specified otherwise, all hoses are manufactured to EN ISO 1307:2006.