



Sawage hose - Blue

Temperature range

-30° C - +50° C

Features

Plasticized PVC hose with superelastic material for low temperature, reinforcement with anti-shock rigid PVC spiral. The special compound of PVC is getting to this hoses super high flexibility and cold weather resistance, that existing conventional hoses have.

Applications

Sink, sparging, tank truck, where a superior flexibility and handling is required. Very useful for general applications on low temperature.

Internal diameter [mm]	Weight [g/m]	Wall thickness [mm]	Bend radius [mm]	Working pressure [bar]	Max. pressure [bar]	Vacuum [m/H ₂ O]	Package [m]	Package Size [m ³]
20	310	3,6	65	7	21	10	30	0,049
25	410	3,8	80	7	21	10	30	0,059
30	550	4,0	100	7	21	10	30	0,074
32	600	4,0	105	7	21	10	30	0,083
35	630	4,2	115	6	18	10	30	0,107
38	700	4,4	125	6	18	10	30	0,127
40	730	4,5	130	6	18	10	30	0,149
45	850	4,5	145	6	18	10	30	0,176
50	1000	4,8	160	5	15	10	30	0,207
52	1000	4,8	160	5	15	9	30	0,207
60	1250	5,0	195	4,5	13,5	9	30	0,288
63	1390	5,2	210	4,5	13,5	9	30	0,288
70	1600	5,5	225	4,5	13,5	9	30	0,388
76	1700	5,5	250	4	12	9	30	0,417
80	1850	6,3	260	3,5	10,5	9	30	0,454
90	2150	6,3	300	3,5	10,5	9	30	0,689
100	2700	6,7	330	3	9	8	30	0,820
105	2700	6,7	335	3	9	8	30	0,820
110	3000	7,0	360	3	9	8	30	0,995
120	3350	7,5	390	2,5	7,5	8	30	1,156
127	3600	7,5	410	2,5	7,5	8	30	1,243
150	5000	9,0	500	2	6	8	20	1,360
160	5600	9,5	550	2	6	8	20	1,500
200	9800	10	850	2	6	7	10	1,880