



AGRABLOW SD /10 240°C

SUCTION AND DELIVERY HOSE FOR HOT AIR FOR ROAD TANKERS



APPLICATION

Suction and delivery hose for hot dry air for road tankers

THRE

White, smooth EPM rubber compound, food quality odourless and taste free

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER

Black, smooth, cloth impression $\ensuremath{\mathbf{EPDM}}$ rubber, resistant to abrasion, ozone and weather

WORKING TEMPERATURE

-40°F +464°F

-40°C +240°C

SPECIFICATIONS

FDA title 21 art.177.2600 (a,b,c,d) for dry foods

									4	2 0	23 22 23
ID		0D		WEIGHT	WP		ВР		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
25	1	36	1 27/64	0.74	10	150	30	450	115	0.9	40
38	1 1/2	49	1 15/16	1.12	10	150	30	450	180	0.9	40
42	1 21/32	53	2 15/16	1.25	10	150	30	450	200	0.9	40
51	2	63	2 31/64	1.70	10	150	30	450	245	0.9	40
63.5	2 1/2	76	3	2.30	10	150	30	450	340	0.9	40
76	3	90	3 35/64	2.75	10	150	30	450	410	0.9	40
90	3 35/64	104	4 15/16	3.79	10	150	30	450	500	0.9	40
102	4	116	4 9/16	4.15	10	150	30	450	580	0.9	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING











