



## APPLICAZIONI

- Tubo multiuso per mandata di vernici, lacche, pitture e solventi affini.

## COSTRUZIONE

### SOTTOSTRATO

- UPE (Polietilene ad altissimo peso molecolare). Neutro, liscio.
- Resistenza: secondo la Tabella delle Resistenze Chimiche MTG.

### RINFORZI

- Inserzioni tessili sintetiche, ad alta resistenza.

### COPERTURA

- Gomma EPDM nera, antistatica ( $R < 10^6 \Omega$ ), resistente all'abrasione, all'ozono e agli agenti atmosferici, liscia, impronta tela.

## MARCATURA



# ALL COLOR

## TEMPERATURE

- Da -35°C a +100°C in funzione ai liquidi convogliati.

## FATTORE DI SICUREZZA

- $\geq 3$  volte la pressione di esercizio.

## APPLICATION

- Universal hose for delivery of paints, varnishes and related solvents.

## CONSTRUCTION

### TUBE

- UPE (ultra High Molecular Weight Polyethylene), neutral, smooth.
- Resistance: according to the MTG Chemical Resistance Chart.

### REINFORCEMENT

- High strength plies of synthetic cord.

### COVER

- EPDM rubber, black, smooth, antistatic ( $R < 10^6 \Omega$ ), resistant to abrasion, ozone and weather, cloth finish.

## MARKING



# ALL COLOR

## TEMPERATURE RANGE

- From -35°C to +100°C depending on the conveyed media.

## SAFETY FACTOR

- $\geq 3$  times working pressure.

## TOLLERANZE DIMENSIONALI / SIZE TOLERANCES:

Diametro interno / I.D. : ISO 1307 - Spessore parete / Wall Thickness : DIN 7715 T4 S2 - Lunghezza / Length : ISO 1307

DIAMETRO INTERNO INTERNAL DIAMETER [mm]	SPESSORE PARETE WALL THICKNESS [mm]	RAGGIO DI CURVATURA BENDING RADIUS [mm]	PRESSIONE DI ESERCIZIO WORKING PRESSURE [bar]	VACUUM VACUUM [bar]	PESO TEORICO THEORETICAL WEIGHT [kg/m]	LUNGHEZZA MAX. LENGTH MAX. [m]
6	3.5	40	18	-0.50	0.12	40
7	3.5	40	18	-0.50	0.13	40
7	4.5	40	18	-0.70	0.18	40
8	3.5	50	18	-0.50	0.14	40
8	4.5	50	18	-0.70	0.20	40
10	3.5	60	18	-0.40	0.17	40
13	3.5	80	18	-0.40	0.21	40
16	3.5	100	18	-0.40	0.24	40
19	5.0	120	18	-0.40	0.41	40
25	5.0	150	18	-0.30	0.52	40
30	6.0	200	18	-0.30	0.75	40
32	6.0	200	18	-0.30	0.75	40

Copertura colorata, non antistatica, disponibile su richiesta (rosso, blu, giallo).  
Upon demand cover available in other colours (red, blue, yellow, not antistatic).