

PREMIUM™ CHEM MASTER EPDM D



REF.									REF.
	mm	mm	mm	Bar	Bar	mm	Kg/m	m	
S-13001	13	25	6	16	64	91	0.5	40	4696-11001
S-13002	19	31	6	16	64	133	0.6	40	4696-11002
S-13003	22	34	6	16	64	154	0.7	40	4696-11003
S-13004	25	37	6	16	64	175	0.7	40	4696-11004
S-13005	32	44	6	16	64	224	0.9	40	4696-11005
S-13006	38	51	6.5	16	64	266	1.2	40	4696-11006
S-13007	50	66	8	16	64	350	1.8	40	4696-11007
S-13008	51	67	8	16	64	357	1.8	40	4696-11008
S-13009	63	79	8	16	64	441	2.2	40	4696-11009
S-13010	75	91	8	16	64	525	2.6	40	4696-11010
	76	92	8	16	64	532	2.7	40	4696-11011
	100	116	8	16	64	700	3.5	40	4696-11012
	101.5	118	8	16	64	714	3.5	40	4696-11013

RECOMMENDED FOR

Premium delivery hose (D) for handling a variety of chemical products such as acids, alkalis, esters and ketones with a medium or low concentration. Tank truck, barge, ship, or storage tank transfer of a variety of mild chemical products.

TUBE

Black EPDM, smooth, conductive

REINFORCEMENT

High tensile synthetic textile cord with crossing anti-static wires

COVER

CSM rubber, black, superior resistance to weather and abrasion, excellent chemical and oil resistance

TEMPERATURE

-40°C to +95°C

BURST PRESSURE

4 x WP

ELECTRICALLY CONDUCTIVE

R < 10⁶ Ohm

STANDARDS

EN 12115

BRANDING TRANSFER LABEL

PREMIUM™ CHEM MASTER EPDM D - EN 12115 CHEMICAL TRANSFER 16 BAR Ω

BRANDING EMBOSSED LABEL

GATES PREMIUM™ CHEM MASTER EPDM D - EN 12115 - EPDM - DIAM .. - 16 BAR - Ω - Q - year

