
















											
mm	mm	kg	CODE	mm	mm	daN											
40	18	0.03	371100	8	21	30											
50	20	0.06	371101	8	22	35											
60	24	0.10	371102	8	28	50											
75	24	0.14	371203	8	28	55											
80	24	0.17	371103	8	28	55											
100	24	0.22	371104	8	28	60											
125	30	0.46	371105	10	35	80											


Institutional brackets



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Swivel actions: double ball ring with grease lubrication
 - 5) King pin: integrated with the plate and cold-rieveted
- Available with total front foot brake


															
mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	daN	
40	18	0.12	374100	0.11	375100	0.15	378100	59	42x42	30x30	5	24	78	30	
50	18	0.20	374101	0.20	375101	0.24	378101	66	55x55	40x40	6	24	76	35	
60	24	0.28	374102	0.26	375102	0.40	378102	82	60x60	45x45	6	21	83	50	
75	24	0.40	374303	0.31	375303	0.48	378303	101	60x60	45x45	6	25	91	55	
80	24	0.43	374103	0.34	375103	0.50	378103	104	60x60	45x45	6	25	91	55	
100	24	0.48	374104	0.40	375104	0.57	378104	121	60x60	45x45	6	32	95	55	
125	30	0.87	374105	0.80	375105	0.97	378105	152	77x67	55x45	8	40	115	80	

Institutional brackets



- 1) Plate: electrolytically galvanised steel plate
- 2) Fork: electrolytically galvanised steel plate
- 3) Ball race ring: electrolytically galvanised steel plate
- 4) Swivel actions: double ball ring with grease lubrication
- 5) King pin: integrated with the plate and cold-riveted


mm		mm	2 pc package		mm		mm	mm	mm	mm	mm	daN
50	18	0.39	374001	66	55x55	40x40	6	24	35	3 km/h		
60	24	0.68	374002	82	60x60	45x45	6	21	50			



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Swivel actions: double ball ring with grease lubrication
 - 5) King pin: integrated with the plate and cold-riveted
- Available with total front foot brake

mm	mm	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	daN
40	18	0.11	373100	0.14	377100	59	35	10	24	78	30	
50	18	0.16	373101	0.19	377101	66	35	10	24	76	35	
60	24	0.25	373102	0.32	377102	82	41	12	21	83	50	
75	24	0.31	373303	0.40	377303	101	41	12	25	91	55	
80	24	0.34	373103	0.43	377103	104	41	12	25	91	55	
100	24	0.40	373104	0.49	377104	121	41	12	32	91	55	
125	30	0.76	373105	0.87	377105	149	55	12	40	115	80	


Institutional brackets



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Galvanised steel threaded stem
 - 5) Swivel actions: double ball ring with grease lubrication
- Available with total front foot brake

mm		kg		CODE		2 pc package		mm		mm		mm		mm		daN	
40	18	0.13	376100	0.18	379100			59	35	M8	15	24	78				30
50	18	0.18	376101	0.21	379101	0.34	376001	66	35	M8	15	24	76				35
60	24	0.29	376102	0.36	379102	0.60	376002	82	41	M12	25	21	83				50
75	24	0.36	376303	0.43	379303			101	41	M12	25	25	91				55
80	24	0.39	376103	0.46	379103			104	41	M12	25	25	91				55
100	24	0.44	376104	0.53	379104			121	41	M12	25	32	95				55
125	30	0.79	376105	0.89	379105			149	52	M12	25	40	115				80


Institutional twin brackets



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Swivel actions: double ball ring with grease lubrication
 - 5) King pin: integrated with the plate and cold-riveted
- Available with total front foot brake

mm		kg		CODE		mm		mm		mm		mm		mm		daN	
50	18+18	0.35	374201	0.40	378201	70	60x60	45x45	6	30	82						60
75	24+24	0.64	374203	0.72	378203	100	60x60	45x45	6	33	95						80

Twin brackets for institutional



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Galvanised steel threaded stem
 - 5) Swivel actions: double ball ring with grease lubrication
- Available with total front foot brake

mm		kg	CODE	kg	CODE	mm		mm	mm	mm	mm	daN
50	18+18	0.30	376201	0.37	379201	70	42	M10	15	30	82	60
75	24+24	0.50	376203	0.68	379203	100	52	M12	25	33	95	80