





















SERIES **73**

SIGMA ELASTIC RUBBER WHEELS WITH POLYAMIDE 6 CENTRE
















																	
mm	mm	kg	CODE	mm	mm.	daN	daN	daN									
100	40	0.31	731102	12	44	200	100	150									
125	40	0.38	731103	15	44	270	150	230									
160	50	0.83	731104	20	59	350	200	300									
180	50	0.90	731105	20	59	400	280	350									
200	50	1.04	731106	20	59	510	350	450									




																	
mm	mm	kg	CODE	kg	CODE	mm	mm	daN	daN	daN							
100	40	0.36	733102	0,36	733202	12	44	200	100	150							
125	40	0.58	733103	0,58	733203	20	44	270	150	230							
160	50	1.04	733104	1.04	733204	20	59	350	200	300							
180	50	1.10	733105	1.10	733205	20	59	400	280	350							
200	50	1.25	733106	1.25	733206	20	59	510	350	450							



																	
mm	mm	kg	CODE	kg	CODE	mm	mm.	mm	mm	daN	daN	daN					
100	40	0.36	732102	0.29	734102	12	40	32	11.5	200	120	150					
125	40	0.58	732103	0.38	734103	20	44	47	17	270	200	230					
160	50	0.99	732104	0.79	734104	20	58	47	17	350	250	300					
160	50	0.94	732114	0.79	734104	25	58	47	17	350	250	300					
180	50	1.05	732105	0.85	734105	20	58	47	17	400	320	350					
180	50	1.00	732115	0.85	734105	25	58	47	17	400	320	350					
200	50	1.12	732106	0.92	734106	20	58	47	17	510	350	450					
200	50	1.07	732116	0.92	734106	25	58	47	17	510	350	450					

Standard-duty brackets NL - max carrying capacity 300 daN



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Dust seal: orange polyethylene
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: integrated with the plate and cold-riveted
- Available with total front foot brake

mm		kg		kg		kg		mm		mm		mm		mm		daN	
100	40	0.85	735002	0.65	735102	0.97	735202	128	100x85	80x60	9	35	120	150			
125	40	1.08	735003	0.81	735103	1.19	735203	156	100x85	80x60	9	37	120	220			
160	50	2.11	735004	1.74	735104	2.36	735204	198	140x110	105x80	11	56	156	300			
180	50	2.22	735005	1.81	735105	2.46	735205	219	140x110	105x80	11	56	156	300			
200	50	2.44	735006	1.98	735106	2.69	735206	240	140x110	105x80	11	56	156	300			
100	40	0.91	735302	0.70	735402	1.02	735502	128	100x85	80x60	9	35	120	150			
125	40	1.23	735303	0.96	735403	1.34	735503	156	100x85	80x60	9	37	120	220			
160	50	2.32	735304	1.89	735404	2.51	735504	198	140x110	105x80	11	56	156	300			
180	50	2.42	735305	1.96	735405	2.61	735505	219	140x110	105x80	11	56	156	300			
200	50	2.65	735306	2.06	735406	2.77	735506	240	140x110	105x80	11	56	156	300			
100	40	0.91	735602	0.70	735702	1.02	735802	128	100x85	80x60	9	35	120	150			
125	40	1.23	735603	0.96	735703	1.34	735803	156	100x85	80x60	9	37	120	220			
160	50	2.32	735604	1.94	735704	2.56	735804	198	140x110	105x80	11	56	156	300			
180	50	2.42	735605	2.01	735705	2.66	735805	219	140x110	105x80	11	56	156	300			
200	50	2.65	735606	2.19	735706	2.89	735806	240	140x110	105x80	11	56	156	300			

Options available to order:



Bracket with directional lock d. 80-125 mm



Directional lock for brackets d. 150-200 mm




Bracket with active centralised brake d. 160-200 mm

SERIES **73**

SIGMA ELASTIC RUBBER WHEELS WITH POLYAMIDE 6 CENTRE

Standard-duty brackets NL - max carrying capacity 300 daN



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) King pin: bushing in electrolytically galvanised steel
 - 5) Swivel actions: double ball ring with grease lubrication
- Available with total front foot brake


mm		kg		kg		mm		mm		mm		mm		daN	
100	40	0.75	737702	0.93	738202	128	73	12	35	120	150				
125	40	0.90	737703	1.11	738203	156	73	12	37	120	220				
160	50	1.43	737704	1.56	738204	193	102	20	56	156	300				
180	50	2.21	737705	2.49	738205	214	102	20	56	156	300				
200	50	2.35	737706	2.63	738206	236	102	20	56	156	300				
100	40	0.81	737802	0.98	738302	128	73	12	35	120	150				
125	40	1.05	737803	1.26	738303	156	73	12	37	120	220				
160	50	1.64	737804	1.77	738304	193	102	20	56	156	300				
180	50	2.41	737805	2.69	738305	214	102	20	56	156	300				
200	50	2.56	737806	2.84	738306	236	102	20	56	156	300				
100	40	0.81	735902	0.98	738402	128	73	12	35	120	150				
125	40	1.05	735903	1.26	738403	156	73	12	37	120	220				
160	50	1.64	735904	1.77	738404	193	102	20	56	156	300				
180	50	2.41	735905	2.69	738405	214	102	20	56	156	300				
200	50	2.56	735906	2.84	738406	236	102	20	56	156	300				

Options available to order:



Bracket with Zamak stem fitted d. 80-125 mm

Standard-duty brackets NL - max carrying capacity 300 daN




- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Solid stem: galvanised steel
 - 5) King pin: bushing in galvanised steel
 - 6) Swivel actions: double ball ring with grease lubrication
- Available with total front foot brake

mm	mm	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	daN
100	40	1.75	738702	1.93	738802	128	73	22	47	35	120	150
125	40	1.90	738703	2.11	738803	156	73	22	47	37	120	220
160	50	2.43	738704	2.56	738804	193	102	26	56	56	156	300
180	50	3.21	738705	3.49	738805	214	102	26	56	56	156	300
200	50	3.35	738706	3.63	738806	236	102	26	56	56	156	300

Stainless steel -standard duty brackets NLX - max carrying capacity 300 daN

INOX




- 1) Plate: AISI 304 stainless steel
 - 2) Fork: AISI 304 stainless steel
 - 3) Ball race ring: AISI 304 stainless steel
 - 4) Dust seal: orange polyamide
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: screw and nut in stainless steel
- Available with total front foot brake

mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	daN	
100	40	0.85	739402	0.65	739502	0.97	739602	128	100x85	80x60	9	35	120	150
125	40	1.08	739403	0.81	739503	1.19	739603	156	100x85	80x60	9	37	120	220
160	50	2.11	739404	1.74	739504	2.36	739604	198	140x110	105x80	11	56	156	300
200	50	2.44	739406	1.98	739506	2.69	739606	240	140x110	105x80	11	56	156	300
100	40	0.91	739702	0.70	739802	1.02	739902	128	100x85	80x60	9	35	120	150
125	40	1.23	739703	0.96	739803	1.34	739903	156	100x85	80x60	9	37	120	220
160	50	2.32	739704	1.89	739804	2.51	739904	198	140x110	105x80	11	56	156	300
200	50	2.65	739706	2.06	739806	2.77	739906	240	140x110	105x80	11	56	156	300

SERIES **73**

**SIGMA ELASTIC RUBBER WHEELS
WITH POLYAMIDE 6 CENTRE**


Medium-duty brackets M - max carrying capacity 450 daN



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Dust seal: blue polyethylene
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: integrated with the plate and cold-rieveted
- Available with adjustable total front foot brake

mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	mm	daN
160	50	2.46	736904	1.74	735104	2.89	737604	198	140x110	105x80	11	58	178	300	
200	50	2.83	736906	1.98	735106	3.24	737606	240	140x110	105x80	11	50	178	450	
160	50	2.67	738904	1.94	735404	3.09	739004	198	140x110	105x80	11	58	178	300	
200	50	3.04	738906	2.19	735406	3.44	739006	240	140x110	105x80	11	50	178	450	
160	50	2.62	739104	1.89	735704	3.04	739204	198	140x110	105x80	11	58	178	300	
200	50	2.91	739106	2.06	735706	3.32	739206	240	140x110	105x80	11	50	178	450	


Medium-heavy duty brackets P - max carrying capacity 450 daN



- 1) Plate: galvanised colonial steel plate
 - 2) Fork: galvanised colonial steel plate
 - 3) Ball race ring: galvanised colonial steel plate
 - 4) Dust seal: orange polyamide
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: steel bolt in grade 8.8 steel and steel nut
- Available with total front foot brake

mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	mm	daN
100	40	1,18	736002	0,69	736102	1,33	736202	138	100x85	80x60	9	46	123	150	
125	40	1,34	736003	0,82	736103	1,48	736203	161	100x85	80x60	9	44	123	230	
100	40	1,23	736302	0,73	736402	1,37	736502	138	100x85	80x60	9	46	123	150	
125	40	1,49	736303	0,97	736403	1,63	736503	161	100x85	80x60	9	44	123	230	
100	40	1,23	736602	0,73	736702	1,37	736802	138	100x85	80x60	9	46	123	150	
125	40	1,49	736603	0,97	736703	1,63	736803	161	100x85	80x60	9	44	123	230	


Medium-heavy duty brackets P - max carrying capacity 450 daN



- 1) Plate: galvanised colonial steel plate
 - 2) Fork: galvanised colonial steel plate
 - 3) Ball race ring: galvanised colonial steel plate
 - 4) Dust seal: orange polyamide
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: steel bolt in grade 8.8 steel and steel nut
- Available with adjustable total rear foot brake

mm		kg		CODE		kg		CODE		kg		CODE		mm		mm		mm		mm		mm		daN																				
160	50	3,18	736004	1,79	736104	3,75	736204	205	140x110	105x80	11	70	126	300	160	50	3,39	736304	1,99	736404	3,91	736504	205	140x110	105x80	11	70	126	300	160	50	3,34	736604	1,99	736704	3,91	736804	205	140x110	105x80	11	70	126	300
180	50	3,29	736005	1,89	736105	3,86	736205	225	140x110	105x80	11	70	126	350	180	50	3,49	736305	2,09	736405	4,06	736505	225	140x110	105x80	11	70	126	350	180	50	3,44	736605	2,04	736705	4,01	736805	225	140x110	105x80	11	70	126	350
200	50	3,54	736006	2,05	736106	4,11	736206	250	140x110	105x80	11	70	126	450	200	50	3,74	736306	2,26	736406	4,31	736506	250	140x110	105x80	11	70	126	450	200	50	3,62	736606	2,13	736706	4,19	736806	250	140x110	105x80	11	70	126	450

Stainless steel medium-heavy duty brackets PX - max carrying capacity 450 daN



INOX

- 1) Plate: AISI 304 stainless steel
 - 2) Fork: AISI 304 stainless steel
 - 3) Ball race ring: AISI 304 stainless steel
 - 4) Dust seal: orange polyamide
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: screw and nut in stainless steel
- Available with adjustable total rear foot brake

mm		kg		CODE		kg		CODE		kg		CODE		mm		mm		mm		mm		mm		daN					
160	50	3,19	737004	1,74	737104	3,76	737204	205	140x110	105x80	11	70	126	300	160	50	3,40	737304	1,94	737404	3,97	737504	205	140x110	105x80	11	70	126	300
180	50	3,36	737005	1,81	737105	3,93	737205	225	140x110	105x80	11	70	126	350	180	50	3,56	737305	2,01	737405	4,13	737505	225	140x110	105x80	11	70	126	350
200	50	3,58	737006	1,98	737106	4,15	737206	250	140x110	105x80	11	70	126	450	200	50	3,78	737306	2,19	737406	4,35	737506	250	140x110	105x80	11	70	126	450