




mm	mm	kg	COD.	kg	COD.	mm	mm	mm	mm	daN	daN	daN	daN	daN
35	27	0,09	752099			6	30	22	7			100		
50	40	0,10	752100	0,04	754100	15	40	35	11			150		
80	40	0,82	752101	0,62	754101	20	40	47	14	450	145		350	240
80	70	1,06	752102	0,82	754102	20	70	47	14	800	250		700	560
80	90	1,35	752105	1,11	754105	20	90	47	14	1000	335		900	720
82	60	0,95	752131	0,75	754131	20	67	47	14	700	310		600	480
82	70	1,09	752132	0,85	754132	20	70	47	14	800	255		700	560
82	70	1,04	752232	0,84	754232	20	70	47	16	800	255		700	560
82	75	1,05	752143	0,85	754143	20	75	47	14	880	300		780	624
82	85	1,27	752134	1,03	754134	20	85	47	14	900	300		800	640
82	90	1,33	752135	1,09	754135	20	90	47	14	1000	340		900	720
82	100	1,45	752137	1,21	754137	20	100	47	14	1100	390		1000	800
85	40	0,72	752121	0,48	754121	20	40	47	14	450	150		400	320
85	70	1,12	752122	0,88	754122	20	70	47	14	800	265		700	560
85	75	1,17	752129	0,93	754129	20	75	47	14	850	285		750	600
85	80	1,25	752123	1,01	754123	20	80	47	14	900	310		800	640
85	80	1,18	752223	0,90	754223	25	80	52	15	900	310		800	640
85	90	1,39	752125	1,15	754125	20	90	47	14	1000	350		900	720
85	100	1,52	752127	1,28	754127	20	100	47	14	1100	400		1000	800

Options available to order



Rollers with customised dimensions

**With labyrinths**



Labyrinths: protective plastic-rings, with interference assembly in front of the ball bearings. They ensure longer life, protecting them from dust and foreign bodies that may limit the roller's free rotation.


mm	mm	kg	CODE	mm	mm	mm	mm	daN	daN	daN	daN				
80	65	0.97	753101	20	70	47	20.5	<b>750</b>	<b>230</b>	<b>650</b>	<b>520</b>				
80	85	1.29	753102	20	90	47	20.5	<b>950</b>	<b>310</b>	<b>850</b>	<b>680</b>				
82	65	1.03	753103	20	70	47	20.5	<b>750</b>	<b>235</b>	<b>650</b>	<b>520</b>				
82	80	1.21	753104	20	85	47	20.5	<b>900</b>	<b>280</b>	<b>800</b>	<b>640</b>				
82	85	1.27	753105	20	90	47	20.5	<b>950</b>	<b>320</b>	<b>850</b>	<b>680</b>				
82	95	1.39	753106	20	100	47	20.5	<b>1050</b>	<b>365</b>	<b>950</b>	<b>760</b>				
85	65	1.06	753107	20	70	47	20.5	<b>750</b>	<b>245</b>	<b>650</b>	<b>520</b>				
85	75	1.19	753108	20	80	47	20.5	<b>850</b>	<b>285</b>	<b>750</b>	<b>600</b>				
85	75	1.12	753223	25	80	47	20.5	<b>850</b>	<b>285</b>	<b>750</b>	<b>600</b>				
85	85	1.33	753109	20	90	47	20.5	<b>950</b>	<b>330</b>	<b>850</b>	<b>680</b>				
85	95	1.46	753110	20	100	47	20.5	<b>1050</b>	<b>375</b>	<b>950</b>	<b>760</b>				

SERIES **75**

**"TR" POLYURETHANE PALLET TRUCK ROLLERS WITH STEEL CENTRE**


**Institutional brackets**

Confezionati



- 1) Plate: electrolytically galvanised steel plate
  - 2) Fork: electrolytically galvanised steel plate
  - 3) Ball race ring: electrolytically galvanised steel plate
  - 4) Swivel actions: double ball ring with grease lubrication
  - 5) King pin: integrated with the plate and cold-riveted
- Available with total front foot brake


mm	mm		CODE	kg	CODE	mm	mm	mm	mm	mm	mm	mm	daN
35	27	0,25	757300	0,27	757400	53	60x60	45x45	6	17	70	100	3 km/h
50	40	0,57	757301	0,63	757401	71,5	60x60	45x45	6	25,5	83	150	



- 1) Plate: electrolytically galvanised steel plate
  - 2) Fork: electrolytically galvanised steel plate
  - 3) Ball race ring: electrolytically galvanised steel plate
  - 4) Swivel actions: double ball ring with grease lubrication
  - 5) King pin: integrated with the plate and cold-riveted
- Available with total front foot brake

mm	mm		CODE	kg	CODE	mm	mm	mm	mm	mm	mm	mm	daN
35	27	0,21	757500	0,24	757600	56	55	10	17	70	100	3 km/h	
50	40	0,56	757501	0,61	757601	71	55	10	25,5	83	150		

**Electrowelded brackets EE MHD - max carrying capacity 800 daN**



- 1) Plate: forged steel with integrated pin
- 2) Fork: deep-drawn legs electro-welded to the flange
- 3) Swivel actions: axial ball bearing and tapered roller bearing
- 4) Grease nipple
- 5) Anti-loosening system nut

mm		kg		COD.		mm		mm		mm		mm		daN		daN	
mm	mm	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	4 km/h	6 km/h	mm	daN	daN	
80	70	3,96	758301	2,98	758401	130	135x110	108x80	11	55	700	560					
85	70	4,02	758311	3,04	758411	132,5	135x110	105x80	11	55	700	560					
85	80	4,15	758321	3,17	758421	132,5	135x110	105x80	11	55	800	640					