












Force required to push or tow a wheel






 	100 kg	200 kg	300 kg	500 kg	600 kg	800 kg	1000 kg
82x60 mm	1.2	2.6	4.5	7	8.7	----	----
82x70 mm	1.2	2.5	3.8	6.5	7.9	10.8	----
82x90 mm	< 1	1.9	2.9	5.5	6	8.4	10.8
82x100 mm	< 1	1.7	2.6	5	5.5	7.5	9.7

For each load and diameter, the table indicates the force (in daN) needed to push or tow a single wheel at the constant speed of 4 km/h on smooth flooring. For manual handling of a 4-wheeled trolley we recommend diameters that have values < 5 daN, for frequent handling we recommend diameters with values < 3 daN.








			CODE		CODE					Static		4 km/h
mm	mm	kg		kg		mm	mm	mm	mm	daN	daN	daN
82	60	0.47	763011	0.23	761011	20	60	47	14	1000	335	700
82	70	0.49	763012	0.25	761012	20	70	47	14	1100	350	850
82	90	0.57	763014	0.33	761014	20	90	47	14	1300	450	1100
82	100	0.65	763015	0.41	761015	20	100	47	14	1400	500	1200



			CODE		
mm	mm	kg		mm	mm
50	55	0.12	760002	12	55



			CODE		
mm	mm	kg		mm	mm
40	43	0.05	760001	17	45

Options available to order



Rollers fitted with 25 mm bore ball bearings