

















Force required to push or tow a wheel

 	100 kg	200 kg	300 kg	400 kg	500 kg	600 kg
82x70 mm	1.1	2.7	5	7.8	----	----
82x90 mm	< 1	2.1	4	6.6	9.7	----
82x100 mm	< 1	1.9	3.5	5.4	7.8	10.5
85x70 mm	< 1	2.5	4.7	7.6	11	----
85x90 mm	< 1	2.3	4	6	8	11

For each load and diameter, the table indicates the force (in daN) needed to push or tow a single roller at the constant speed of 4 km/h on smooth floor. For manual handling of a trolley choose diameters that have values < 5 daN, for frequent handling choose values < 3 da N.



													
mm	mm	kg	CODE	kg	CODE	mm	mm	mm	mm	daN	daN	daN	daN
82	70	0.60	772132	0.36	774132	20	70	47	14	<b>550</b>	<b>300</b>	<b>450</b>	<b>360</b>
82	90	0.70	772135	0.46	774135	20	90	47	14	<b>610</b>	<b>340</b>	<b>510</b>	<b>400</b>
82	100	0.76	772137	0.52	774137	20	100	47	14	<b>700</b>	<b>380</b>	<b>600</b>	<b>480</b>
85	70	0.65	772122	0.41	774122	20	70	47	14	<b>600</b>	<b>310</b>	<b>500</b>	<b>400</b>
85	90	0.76	772125	0.52	774125	20	90	47	14	<b>700</b>	<b>350</b>	<b>600</b>	<b>480</b>

Options available to order



Rollers fitted with 25 mm bore ball bearings