

CORDPLAST®

PRESSCORD PU POLYURETHANE

mm	mm	gr/mt	bar	bar
6	10	70	20	60
8	12	85	20	60
10	15	135	20	60
13	19	195	20	60

TEMPERATURE, TEMPERATUR, TEMPERATURA, TEMPERATURE: -10°C / +60°C
+14°F / +140°F

NORMS, NORMEN. NORMAS, NORMES EEC DIRECTIVE: ISO 1307

LENGHT/LANGE/LONGITUD/LONGUEUR: mt 100



Tube: black PU compound.

Reinforcement: high tensile synthetic textile.

Cover: abrasion, ozone and weather resistant pvc compound.

Application: high performance transfer of air, oils and light chemicals.



Seele: schwarz, PU-qualität.

Einlagen: hochfestes synthetisches textildgewebe.

Decke: abriebfester, ozon- und witterungsbeständiger, pvc.

Anwendung: hochleistungsförderschlauch für luft, öl und leichte chemikalien.



Sustrato: manguera en PU, negra.

Refuerzo: inserciones textiles con alta resistencia.

Cobertura: pvc, resistente a la abrasión, ozono y agentes atmosféricos.

Uso: de uso pesado de aire, aceites, a varios productos químicos.



Tube: tuyau noir en PU.

Renforcement: insertion textile haute tenacite.

Revetement: lisse, en pvc souple resistente a l'abrasion, et les agents atmospheriques.

Application: performance de transfert elevee de l'air, les huiles et produits chimiques nonagressives

SATI GROUP S.P.A.

Via C. Bonazzi, 24 - 40013 CASTEL MAGGIORE (BO) - ITALY

Tel. +39.051.700321 - Fax +39.051.701350

E-mail: export@satigroup.it

web: www.satigroup.it